## **SOLIDEAL ECOMATIC TRACTION**

**BY CAMSO** 



PRESS-ON TIRES



### PERFORMANCE WHEN YOU NEED IT.

Best-in-class and ideal for low-intensity material handling applications. With its natural rubber compounds it delivers maximum life where premium technology is not required.

### PERFORMANCE

ENERGY SAVINGS
TIRE LIFE





FORMERLY CAMOPLAST SOLIDEAL

# **SOLIDEAL ECOMATIC TRACTION**

BY CAMSO

TIRE SIZE (1)	ACTUAL TIRE DIMENSIONS			LOAD CAPACITY <sup>(2)</sup> Counterbalanced lift trucks (lbs)					
	OVERALL DIAMETER	OVERALL WIDTH	REPLACEMENT OVERALL DIAMETER <sup>(3)</sup> (in)	6 mph		10 mph		16 mph	
	(in)	(in)		LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
14 x 4 1/2 x 8	13.9	4.5	12.1	2568	2105	2293	1929	1863	1532
16 x 5 x 10 1/2	15.9	5.0	14.3	3318	2734	2965	2491	2414	1973
16 x 6 x 10 1/2	15.9	6.0	14.3	4200	3450	3748	3153	3053	2502
16 1/4 x 5 x 11 1/4	16.1	5.0	14.7	3362	2756	2998	2524	2436	1995
16 1/4 x 6 x 11 1/4	16.1	6.0	14.7	4222	3461	3770	3164	3064	2513
18 x 6 x 12 1/8	17.9	6.0	16.1	4608	3781	4112	3450	3340	2745
18 x 7 x 12 1/8	17.9	7.0	16.1	5633	4630	5026	4222	4090	3351
18 x 8 x 12 1/8	17.9	8.0	16.1	6614	5434	5908	4960	4806	3935
21 x 7 x 15	20.9	7.0	19.1	6327	5203	5655	4751	4597	3770
21 x 8 x 15	20.9	8.0	19.1	7441	6118	6647	5578	5401	4431
22 x 9 x 16	21.8	9.0	20.1	8918	7330	7970	6691	6482	4718

#### **HUGE LUG DEPTH**

Increases life and traction

#### **NATURAL RUBBER COMPOUND**

 Provides good overall wear and performance

#### AVAILABLE IN NON-MARKING COMPOUND



#### Remarks

- (1) Tolerances on wheel diameter Code designated sizes (in): nominal rim diameter +0.005"/-0" Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3 μm Chamfer 5 mm wide @ 30°
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.
- (3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter. All specifications for non-marking tires are the same as the equivalent standard black tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

#### AUTHORIZED DISTRIBUTOR:



3305 Robertson Road Tyler, TX 75701

T: 800.873.1828 P: 903.533.9600

F: 903.533.9927

E: info@lifttrucksupplyinc.com



To keep moving forward while staying true to our history, we're now the Road Free company.





FORMERLY CAMOPLAST SOLIDEAL